

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**GW StyleSign Texturizer**  
**Article number 227527-200ml / 227587-25ml**

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**1.2.1 Relevant uses**

hair treatment

**1.2.2 Uses advised against**

None known.

**1.3 Details of the supplier of the safety data sheet**

**Company** KAO USA Inc.  
2535 Spring Grove Avenue  
Cincinnati, Ohio 45214 / USA  
Phone

**Address enquiries to**

**Technical information**

**Safety Data Sheet** sdb@chemiebuero.de

**1.4 Emergency telephone number**

**Company** CHEMTREC: +1 703 527-3887 (24h)

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Flam. Liq. 3: H226 Flammable liquid and vapor.

**2.2 Label elements**

The product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200 (HCS 2012)  
This preparation is excluded as cosmetics for labelling requirements of 29 CFR 1910.1200-HCS 2012 in accordance to (b)(5)(iii).

**Special labelling**

**2.3 Other hazards**

**Physico-chemical hazards**

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

**Other hazards**

Further hazards were not determined with the current level of knowledge.

### SECTION 3: Composition / Information on ingredients

#### Product-type:

The product is a mixture.

Range [%]	Substance
5 - 10	Ethanol
	CAS: 64-17-5, EINECS/ELINCS: 200-578-6, EU-INDEX: 603-002-00-5, Reg-No.: 01-2119457610-43-XXXX
	GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319
< 1	Propan-2-ol
	CAS: 67-63-0, EINECS/ELINCS: 200-661-7, EU-INDEX: 603-117-00-0, Reg-No.: 01-2119457558-25-XXXX
	GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319 - STOT SE 3: H336
0,1 - < 0,2	Sulisobenzone
	CAS: 4065-45-6, EINECS/ELINCS: 223-772-2
	GHS/CLP: Skin Irrit. 2: H315 - Eye Irrit. 2: H319 - Skin Sens. 1B: H317

#### Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%.  
For full text of H-statements: see SECTION 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information

Change soaked clothing.

##### Inhalation

Ensure supply of fresh air.  
In the event of symptoms seek medical treatment.

##### Skin contact

In case of contact with skin wash off immediately with soap and water.  
Consult a doctor if skin irritation persists.

##### Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.

##### Ingestion

Consult a doctor immediately.  
Rinse out mouth and give plenty of water to drink.  
Do not induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.  
Forward this sheet to the doctor.

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Alcohol-resistant foam.  
Dry powder.  
Carbon dioxide.  
Water spray jet.

##### Extinguishing media that must not be used

Full water jet.

#### 5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

#### 5.3 Advice for firefighters

Use self-contained breathing apparatus.  
Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.  
Keep away from all sources of ignition.

### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).  
Dispose of absorbed material in accordance within the regulations.

### 6.4 Reference to other sections

See SECTION 8+13

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

No special measures necessary if used correctly.  
Keep away from all sources of ignition - Refrain from smoking.  
Do not eat, drink or smoke when using this product.  
Wash hands before breaks and after work.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.  
Do not store together with oxidizing agents.  
Keep container tightly closed.  
Protect from heat/overheating.

### 7.3 Specific end use(s)

See product use, SECTION 1.2

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Ingredients with occupational exposure limits to be monitored (US)**

Substance
Ethanol
CAS: 64-17-5, EINECS/ELINCS: 200-578-6, EU-INDEX: 603-002-00-5, Reg-No.: 01-2119457610-43-XXXX
Long-term exposure: 1000 ppm, 1900 mg/m <sup>3</sup> , OSHA, NIOSH
Propan-2-ol
CAS: 67-63-0, EINECS/ELINCS: 200-661-7, EU-INDEX: 603-117-00-0, Reg-No.: 01-2119457558-25-XXXX
Long-term exposure: 200 ppm, 500 mg/m <sup>3</sup> , INRS, NIOSH

**DNEL**

Substance
Propan-2-ol, CAS: 67-63-0
Industrial, dermal, Long-term - systemic effects: 888 mg/kg.
Industrial, inhalative, Long-term - systemic effects: 500 mg/m <sup>3</sup> .
general population, oral, Long-term - systemic effects: 26 mg/kg.
general population, inhalative, Long-term - systemic effects: 89 mg/m <sup>3</sup> .
general population, dermal, Long-term - systemic effects: 319 mg/kg.
Ethanol, CAS: 64-17-5
Industrial, inhalative, Long-term - systemic effects: 950 mg/m <sup>3</sup> .
Industrial, inhalative, Acute - local effects: 1900 mg/m <sup>3</sup> .
Industrial, dermal, Long-term - systemic effects: 343 mg/kg bw/d.
general population, inhalative, Long-term - systemic effects: 114 mg/m <sup>3</sup> .
general population, inhalative, Acute - local effects: 950 mg/m <sup>3</sup> .
general population, dermal, Long-term - systemic effects: 206 mg/kg bw/d.
general population, oral, Long-term - systemic effects: 87 mg/kg bw/d.

**PNEC**

Substance
Propan-2-ol, CAS: 67-63-0
soil, 28 mg/kg.
sediment (seawater), 552 mg/kg.
sediment (freshwater), 552 mg/kg.
seawater, 140,9 mg/l.
freshwater, 140,9 mg/l.
Ethanol, CAS: 64-17-5
oral (food), 0,72 mg/kg.
soil, 0,63 mg/kg.
sediment (freshwater), 3,6 mg/kg.
seawater, 0,79 mg/l.
freshwater, 0,96 mg/l.

## 8.2 Exposure controls

<b>Additional advice on system design</b>	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
<b>Eye protection</b>	Not required under normal conditions. If there is a risk of splashing: Safety glasses. (EN 166:2001)
<b>Hand protection</b>	The details concerned are recommendations. Please contact the glove supplier for further information. In full contact: 0,4 mm: butyl rubber, > 120 min (EN 374)
<b>Skin protection</b>	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals.  Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes. Do not inhale vapors.
<b>Respiratory protection</b>	Not required under normal conditions.
<b>Thermal hazards</b>	none
<b>Delimitation and monitoring of the environmental exposition</b>	Comply with applicable environmental regulations limiting discharge to air, water and soil.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>Form</b>	liquid
<b>Color</b>	colourless light yellow
<b>Odor</b>	characteristic
<b>Odor threshold</b>	not applicable
<b>pH-value</b>	6,2 - 6,5
<b>pH-value [1%]</b>	not determined
<b>Boiling point [°C]</b>	not determined
<b>Flash point [°C]</b>	54 / 129°F
<b>Flammability [°C]</b>	not determined
<b>Lower explosion limit</b>	not determined
<b>Upper explosion limit</b>	not determined
<b>Oxidizing properties</b>	no
<b>Vapor pressure/gas pressure [kPa]</b>	not determined
<b>Density [g/ml]</b>	1,002 - 1,006 (20 °C / 68,0 °F)
<b>Bulk density [kg/m³]</b>	not applicable
<b>Solubility in water</b>	immiscible
<b>Partition coefficient [n-octanol/water]</b>	not determined
<b>Viscosity</b>	not determined
<b>Relative vapor density determined in air</b>	not determined
<b>Evaporation speed</b>	not determined
<b>Melting point [°C]</b>	not determined
<b>Autoignition temperature [°C]</b>	not applicable
<b>Decomposition temperature [°C]</b>	not determined

### 9.2 Other information

Refractometer factor: 1,3300 - 1,3500

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reactions known if used as directed.

### 10.2 Chemical stability

The product is stable under standard conditions.

### 10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

### 10.4 Conditions to avoid

See SECTION 7.2.

Strong heating.

### 10.5 Incompatible materials

No information available.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity**

Substance
Propan-2-ol, CAS: 67-63-0
LD50, dermal, Rabbit: 12800 mg/kg (RTECS).
LD50, oral, Rat: 5045 mg/kg (RTECS).
LC50, inhalative, Rat: 46,5 mg/l (4h).
LDLo, oral, Human: 3570 mg/kg (RTECS).
Sulisobenzone, CAS: 4065-45-6
LD50, oral, Rat: > 2000 mg/kg.
Ethanol, CAS: 64-17-5
LD50, dermal, Rabbit: > 2000 mg/kg (OECD 402).
LD50, oral, Rat: 10470 mg/kg (OECD 401).
LC50, inhalative, Rat: 117-125 mg/l/4h (OECD 403).
NOAEL, Rat: > 3000 mg/kg/d (24 month OECD 451).

<b>Serious eye damage/irritation</b>	Based on the information available, the classification criteria have not been fulfilled.
<b>Skin corrosion/irritation</b>	Based on the information available, the classification criteria have not been fulfilled.
<b>Respiratory or skin sensitisation</b>	Based on the information available, the classification criteria have not been fulfilled.
<b>Specific target organ toxicity — single exposure</b>	Based on the information available, the classification criteria have not been fulfilled.
<b>Specific target organ toxicity — repeated exposure</b>	Based on the information available, the classification criteria have not been fulfilled.
<b>Mutagenicity</b>	Based on the information available, the classification criteria have not been fulfilled.
<b>Reproduction toxicity</b>	Based on the information available, the classification criteria have not been fulfilled.
<b>Carcinogenicity</b>	Based on the information available, the classification criteria have not been fulfilled.
<b>Aspiration hazard</b>	Based on the information available, the classification criteria have not been fulfilled.
<b>General remarks</b>	

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials. This is a cosmetic product that is safe under intended and reasonable foreseeable use. Taking into account the use instructions, the toxicological profile of the ingredients and the evaluation of the final formulation this product is considered as safe and thus not harming human health.

## SECTION 12: Ecological information

### 12.1 Toxicity

Substance
Propan-2-ol, CAS: 67-63-0
LC50, (96h), <i>Lepomis macrochirus</i> : 1400 mg/l (ECOTOX Database).
EC50, (48h), <i>Daphnia magna</i> : 13299 mg/l (IUCLID).
IC50, (72h), <i>Desmodesmus subspicatus</i> : >1000 mg/l (IUCLID).
EC5, (16h), <i>Pseudomonas putida</i> : 1050 mg/l (Lit.).
EC5, (72h), fish: 4930 mg/l (Lit.).
Sulisobenzone, CAS: 4065-45-6
LC50, (96h), <i>Leuciscus idus</i> : > 220 mg/l.
Ethanol, CAS: 64-17-5
LC50, (96h), <i>Oncorhynchus mykiss</i> : 13000 mg/l (OECD 203).
LC50, (48h), <i>Daphnia magna</i> : 12340 mg/l.
EC50, (72h), Algae: 275 mg/l (OECD 201).
EC50, (48h), <i>Selenastrum capricornutum</i> : 12900 mg/l (OECD 201).

### 12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

### 12.3 Bioaccumulative potential

not determined

### 12.4 Mobility in soil

not determined

### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

### 12.6 Other adverse effects

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product	For recycling, consult manufacturer. Disposal in an incineration plant in accordance with the regulations of the local authorities.
Contaminated packaging	Uncontaminated packaging may be taken for recycling.
RCRA Hazard Class (40CFR 261)	Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities.

**SECTION 14: Transport**

**14.1 UN number**

Transport by land according to ADR/RID 1993

DOT Road Shipment Information (49 CFR) 1993

Marine transport in accordance with IMDG 1993

Air transport in accordance with IATA 1993

**14.2 UN proper shipping name**

Transport by land according to ADR/RID Entzündbarer flüssiger Stoff, n.a.g. (Ethanol, Isopropanol)

- Classification Code F1

- Label 

- ADR LQ 5 l

- ADR 1.1.3.6 (8.6) Transport category (tunnel restriction code) 3 (D/E)

DOT Road Shipment Information (49 CFR) Flammable liquid, n.o.s. (Ethanol, Isopropanol)

- Label 


Marine transport in accordance with IMDG Flammable liquid, n.o.s. (Ethanol, Isopropanol)

- EMS F-E, S-E

- Label 

- IMDG LQ 5 l

Air transport in accordance with IATA Flammable liquid, n.o.s. (Ethanol, Isopropanol-mixture)

- Label 

**14.3 Transport hazard class(es)**

Transport by land according to ADR/RID 3

DOT Road Shipment Information (49 CFR) 3

Marine transport in accordance with IMDG 3

Air transport in accordance with IATA 3

#### 14.4 Packing group

Transport by land according to ADR/RID III

DOT Road Shipment Information (49 CFR) III

Marine transport in accordance with IMDG III

Air transport in accordance with IATA III

#### 14.5 Environmental hazards

Transport by land according to ADR/RID no

DOT Road Shipment Information (49 CFR) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

#### 14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not determined

### SECTION 15: Regulatory information

#### US Regulations

##### National regulations

29 CFR 1910.1200-HCS 2012, OSHA-PEL, ACGIH-TLV, NTP, IARC, SARA Title III, NFPA, TSCA, California - Prop. 65

- SARA, 302

This product is not classified as hazardous under SARA 302.

- SARA, 311

This product is classified as hazardous under SARA 311.

- SARA, 313

One or more ingredient(s) are listed under this regulation.

- CA Proposition 65

No chemical substances in this material are named on the California P65 list.

- TSCA

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory.

- FDA

not determined

American Conference of Governmental Industrial Hygienists - ACGIH'

Ingredients not listed as carcinogens.

International Agency for Research on Cancer IARC

not determined

National Toxicology Program - NTP'

not determined

HAP-VOC

dÃ

Transport-regulations

DOT-Classification, ADR (2015); IMDG-Code (2015, 37. Amdt.); IATA-DGR (2016).

### SECTION 16: Other information

#### 16.1 Hazard statements (SECTION 03)

H317 May cause an allergic skin reaction.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H319 Causes serious eye irritation.

H225 Highly flammable liquid and vapor.

## 16.2 Abbreviations and acronyms:

ACGIH = American Conference of Governmental Industrial Hygienists;  
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route;  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses;  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure;  
CAS = Chemical Abstracts Service;  
CERCLA = Comprehensive Environmental Response, Compensation and Liability Act;  
CFR = Code of Federal Regulations;  
CPR = Controlled Products Regulations;  
DMEL = Derived Minimum Effect Level;  
DNEL = Derived No Effect Level;  
DOT = Department of Transportation;  
EC50 = Median effective concentration;  
EPA = Environmental Protection Agency;  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals;  
IATA = International Air Transport Association;  
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk;  
IC50 = Inhibition concentration, 50%;  
IMDG = International Maritime Code for Dangerous Goods;  
IARC = International Agency of Research on Cancer;  
IATA = International Air Transport Association;  
TSCA = Toxic Substance Control Act;  
HMIS = Hazardous Materials Identification System;  
NFPA = National Fire Protection Association;  
NIOSH = National Institute for Occupational Safety and Health;  
OSHA = Occupational Safety and Health Administration;  
LC50 = Lethal concentration, 50%;  
LD50 = Median lethal dose, 50%;  
MARPOL = International Convention for the Prevention of Marine Pollution from Ships;  
PBT = Persistent, Bioaccumulative and Toxic substance;  
PNEC = Predicted No-Effect Concentration;  
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals;  
SARA = Superfund Amendments and Reauthorization Act;  
TLV@/TWA = Threshold limit value – time-weighted average;  
TLV@STEL = Threshold limit value – short-time exposure limit;  
VOC = Volatile Organic Compounds;  
vPvB = very Persistent and very Bioaccumulative;

## 16.3 Ratings

### HMIS Ratings

HEALTH	1	1 - Slight Hazard
FLAMMABILITY	2	2 - Moderate Hazard
PHYSICAL HAZARD	0	0 - Minimal Hazard
PERSONAL PROTECTION	X	X - Personal protection rating to be supplied by user depending on use conditions

### NFPA Ratings

2
1 0
-

TOP, FLAMMABILITY: 2 - Moderate Hazard  
LEFT, HEALTH: 1 - Slight Hazard RIGHT, REACTIVITY: 0 - Minimal Hazard  
BOTTOM, SPECIAL NOTICE: -