

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

PRODUCT NAME: TCA – The Color Accelerator
PRODUCT CODE: ACO006
SUGGESTED USE: Hair care
RESTRICTIONS USE: N/A
MANUFACTURER: Product Packaging West, Inc.
11921 Vose Street
North Hollywood, CA 91605
TELEPHONE: 1-818-765-8037
DISTRIBUTOR: Dennis Bernard, Inc.
142 Ely Harmony Road
Freehold, NJ 07728
TELEPHONE: 1-561-989-4415
FAX: 1-732-308-9608
EMERGENCY PHONE: Dennis Bernard: 1-561-989-4415

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION: Aspiration Hazard – Category 1
SIGNAL WORD: Danger
HAZARD STATEMENTS: H304 – Maybe fatal if swallowed and enters airways.
PICTOGRAMS:



PRECAUTIONARY STATEMENTS: P301 & P310 & P331 – If swallowed: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
P405 – Store locked up.
P501 – Dispose of contents/containers to approved disposal facility.

HAZARDS NOT OTHERWISE CLASSIFIED: None known.
See toxicological information (Section 11)

SAFETY DATA SHEET

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT:	CAS NUMBER:	CONCENTRATION:
White Mineral Oil	8042-47-5	<90%

Any concentration shown as a range is to protect confidentiality.

There are no additional ingredients which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment hence requires reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: FIRST AID MEASURES

IF INHALED:	If inhaled, move person into fresh air. If not breathing, give artificial respiration. Consult a physician if symptoms are experienced.
SKIN CONTACT:	Flush skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and shoes. If irritation persists, consult a physician.
EYE CONTACT:	Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses if able to do so. Immediately call a doctor or physician.
IF INGESTED:	Do not induce vomiting unless instructed to do so by a physician. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABILITY OVERVIEW:	Low flammability risk.
FLASH POINT:	>177 °C (350 °F)
SUITABLE EXTINGUISHING MEDIA	Use water-spray, alcohol-resistant foam, dry chemical, or carbon dioxide. Alcohol-resistant foam is recommended for large fires.

SAFETY DATA SHEET

UNSUITABLE EXTINGUISHING
MEDIA:

For large fires: Wear a self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) and full protective gear. Fight fires from a safe distance or protected areas

SPECIAL PROTECTIVE EQUIPMENT
FOR FIREFIGHTERS:

Sealed containers can explode in the heat of a fire. Vapors can travel a long distance to ignition sources and ignite.

HAZARDOUS COMBUSTION
PRODUCTS:

Carbon Monoxide, Carbon Dioxide, and unidentified organic compounds.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Provide adequate ventilation.

ENVIRONMENTAL PRECAUTIONS:

Avoid over-dispersal of spilled material and runoff contact with soil, waterways, drains, and sewers.

CONTAINMENT AND CLEAN UP:

Soak up with inert absorbent material and dispose of. Keep in suitable, closed containers for disposal. If assistance is needed, call emergency services.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING:

Avoid over-exposure, read instructions before use. Avoid exposure during pregnancy. Do not use until all safety precautions have been read and understood. Do not get in eyes. Do not ingest. Avoid over-inhalation. Use only with adequate ventilation. Do not enter storage areas and confined spaces unless adequately ventilated. Keep the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Do not reuse container.

SAFE STORAGE:

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for

SAFETY DATA SHEET

use. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

COMPONENT:	CAS NUMBER:	EXPOSURE LIMIT	BASIS
White Mineral Oil	8042-47-5	10 mg/m ³	ACGIH TWA
		5 mg/m ³	OSHA PEL

PERSONAL PROTECTIVE EQUIPMENT

EYE PROTECTION:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
HAND PROTECTION:	Handle with chemical-resistant gloves. Gloves must be inspected prior to use. Wash and dry hands after use.
SKIN PROTECTION:	Wear long sleeves, a chemical apron, or other protective clothing to prevent skin contact. Safety showers should be located in the work area where skin contact can occur.
RESPIRATORY PROTECTION:	Always ensure adequate ventilation. Where risk assessment shows air-purifying respirators are appropriate, use a NIOSH-approved full-face respirator with appropriate cartridges. Respiratory protection must be provided in accordance with OSHA 29 CFR 1910.134.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid.
COLOR:	Clear, colorless
ODOR:	Odorless.
ODOR THRESHOLD:	Not available.
pH:	Not tested.
MELTING / FREEZING POINT:	<-18 °C (0°F)
BOILING POINT:	>260 °C (500°F)
FLASH POINT:	>155 °C (311°F)

SAFETY DATA SHEET

EVAPORATION RATE:	Not available.
FLAMMABILITY (SOLID, GAS)	Not available.
FLAMMABILITY / EXPLOSION LIMIT:	Not available.
VAPOR PRESSURE @ 20 °C	<0.01 mmHg
VAPOR DENSITY:	>1 (air=1)
SPECIFIC GRAVITY:	0.94-0.96
DENSITY:	7.84- 8.01 lbs/gal
SOLUBILITY IN WATER:	Insoluble
PARTITION COEFFICIENT:	Not available.
AUTOIGNITION TEMPERATURE:	Not available.
DECOMPOSITION TEMPERATURE:	Not available.
VISCOSITY:	<500 cPs

SECTION 10: STABILITY AND REACTIVITY

	Stable under recommended storage conditions.
CHEMICAL STABILITY:	
CONDITIONS AND MATERIALS TO AVOID:	Avoid heat, fire, open flames, direct light, and ignition sources. Avoid strong acids or oxidizing agents, such as chlorates, nitrates, peroxides, etc.
HAZARDOUS DECOMPOSITION PRODUCTS:	Not anticipated under conditions of normal use.

SECTION 11: TOXICOLOGICAL INFORMATION**ACUTE TOXICITY**

COMPONENT	CAS NUMBER	TEST	TOXICITY
White Mineral Oil	8042-47-5	Oral LD50 (rat)	>5000 mg/kg
		Dermal LD50 (rat)	>2000 mg/kg
		Inhalation LC50 (rat)	>5mg/L (4hr)

POTENTIAL HEALTH EFFECTS

INHALATION:	Can be harmful if inhaled. Avoiding breathing vapors of the heated liquid.
SKIN:	Can cause skin irritation.
EYES:	May cause eye irritation.

SAFETY DATA SHEET

INGESTION:	Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea. Aspiration hazard.
SIGNS AND SYMPTOMS OF EXPOSURE:	Irritation.
CHRONIC EFFECTS OF LONG-TERM EXPOSURE:	Not available.
CARCINOGENICITY:	Not available.
MUTAGENICITY:	Not available.

SECTION 12: ECOLOGICAL INFORMATION**ACUTE ECOTOXICITY**

CAS NUMBER	CAS NUMBER	TEST	TOXICITY
White Mineral Oil	8042-47-5	Oncorhynchus mykiss	LC50 > 5000 mg/L (96hr)
		Daphnia magna	EC50 >1000 mg/L (48hr)

ECOLOGICAL EFFECTS

PERSISTENCE AND DEGRADABILITY:	Per the IOPC Fund definition: persistent.
BIOACCUMULATION POTENTIAL:	Not expected to bio-accumulate.
MOBILITY IN SOIL:	No data available.
OTHER ADVERSE EFFECTS:	None expected.

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
CONTAMINATED PACKAGING:	Disposed of unused product.

SAFETY DATA SHEET

SECTION 14: TRANSPORTATION INFORMATION

UN NUMBER:	Not available.
UN PROPER SHIPPING NAME:	Not available.
TRANSPORT HAZARD CLASSES:	Not available.
SUB RISK:	Not available.
PACKING GROUP:	Not available.
ENVIRONMENTAL HAZARDS:	No.

SECTION 15: REGULATORY INFORMATION**US FEDERAL**

SARA 302 COMPONENTS:	None listed
SARA 311/312:	None listed
SARA 313 COMPONENTS:	None listed
TSCA INVENTORY:	All chemicals listed or exempted.

EUROPEAN UNION

EC INVENTORY:	EINECS 232-455-8
---------------	------------------

STATE REGULATIONS

CA PROP 65:	CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986. This product is not known to the State of California to cause cancer, birth defects or other reproductive harm.
-------------	--

SECTION 16: OTHER INFORMATION

SDS VERSION:	06-22-2015
REVISION DATE:	N/A

Notice to reader: To the best of our knowledge, the information contain herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

SAFETY DATA SHEET

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.