

1. Identification

Product identifier	Isopropyl Alcohol 70%	
Other means of identification		
Synonyms	Isopropanol (70% v/v) and water solution	
Recommended use	General purpose solvent	
Recommended restrictions	None known	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	maxill Inc.	
Address	80 Elm Street St. Thomas, ON N5R 6C8 Canada	
Telephone	519-631-7370 Fax: 519-631-3388 Website: maxill.com	
E-mail	Not available.	
Emergency phone number	CANUTEC 1-888-226-8832 CHEMTEL (Emergency Response) +01-813-248-0585	
Supplier	See above.	

2. Hazard identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		



Signal word	Danger	
Hazard statement	Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.	
Precautionary statement		
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective clothing, eye protection and face protection. Wash thoroughly after handling. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area.	
Response	In case of fire: Use carbon dioxide, dry chemical, water spray, or foam to extinguish. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.	
Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.	
Disposal	Dispose of container in accordance with local, regional, national and international regulations.	
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known	
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known	

Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/Information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Isopropanol		67-63-0	60 - 80 *

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Product intended to be used on skin.
Eye contact	Avoid contact with eyes. If contact occurs, rinse thoroughly with water.
Ingestion	Not intended for ingestion. Product is naturally bitter. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Rinse mouth. Obtain medical attention.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes.

5. Fire-fighting measures

Suitable extinguishing media	Carbon dioxide. Water spray. Alcohol resistant foam. Dry chemical.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
----------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Avoid contact with eyes.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/Personal protection

Occupational exposure limits**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	984 mg/m ³ 400 ppm
	TWA	492 mg/m ³ 200 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1230 mg/m ³ 500 ppm
	TWA	983 mg/m ³ 400 ppm

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Isopropanol (CAS 67-63-0)	15 minute	400 ppm
	8 hour	200 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Isopropanol (CAS 67-63-0)	PEL	980 mg/m ³ 400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm
	TWA	980 mg/m3
		400 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/L	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection	Not normally required.
Skin protection	
Hand protection	Not normally required when used as directed. When handling in large quantities or responding to emergency situations, the use of appropriate skin protection is recommended.
Other	As required by employer code.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.

9. Physical and chemical properties

Appearance	Clear
Physical state	Liquid.
Form	Liquid.
Color	Colorless
Odor	Isopropanol
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	172.4 °F (78 °C)
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	66.2 °F (19.0 °C) Closed cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure/density	Not available.
VOC Content	557 g/L
Relative density	0.87
Solubility(ies)	Not available.

Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not mix with other chemicals.
Incompatible materials	Strong oxidizing agents. Acids.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological information

Routes of exposure	Eye, Skin contact, Inhalation, Ingestion.
Information on likely routes of exposure	
Ingestion	Not intended for ingestion. Product is naturally bitter. May cause stomach distress, nausea or vomiting.
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
Isopropanol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	13900 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Rat	25000 mg/m ³ , 6 Hours, ECHA 16970 mg/l/4h, HMIRA
<i>Oral</i>		
LD50	Rat	5840 mg/kg, ECHA

Skin corrosion/irritation Not expected to be a primary skin irritant.

Exposure minutes Not available.

Erythema value Not available.

Oedema value Not available.

Serious eye damage/eye irritation Causes serious eye irritation.

Corneal opacity value Not available.

Iris lesion value Not available.

Conjunctival reddening value Not available.

Conjunctival oedema value Not available.

Recover days Not available.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization	This product is not expected to cause skin sensitization.
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Not classified.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Teratogenicity	Not available.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	See below		
Ecotoxicological data			
Components		Species	Test Results
Isopropanol (CAS 67-63-0)			
Algae	IC50	Algae	1000 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Aquatic			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	> 1400 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.		
Bioaccumulative potential			
Mobility in soil	No data available.		
Mobility in general	Not available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
-------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	UN1219
Proper shipping name	Isopropanol
Hazard class	3
Packing group	II
Special provisions	IB2, T4, TP1
Packaging exceptions	4b, 150

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	UN1219
Proper shipping name	ISOPROPANOL

Hazard class 3
Packing group II

DOT



TDG



15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Isopropanol (CAS 67-63-0) 1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Limited quantity, permitting.

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Isopropanol (CAS 67-63-0) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA) No

SARA 302 Extremely hazardous substance

Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

Classified hazard categories

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Isopropanol	67-63-0	60 - 80 *

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations See below

US - California Hazardous Substances (Director's): Listed substance

Isopropanol (CAS 67-63-0) Listed.

US - Illinois Chemical Safety Act: Listed substance

Isopropanol (CAS 67-63-0)

US - Louisiana Spill Reporting: Listed substance

Isopropanol (CAS 67-63-0) Listed.

US - Minnesota Haz Subs: Listed substance

Isopropanol (CAS 67-63-0) Listed.

US - Texas Effects Screening Levels: Listed substance

Isopropanol (CAS 67-63-0) Listed.

US. Massachusetts RTK - Substance List

Isopropanol (CAS 67-63-0)

US. New Jersey Worker and Community Right-to-Know Act

Isopropanol (CAS 67-63-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Isopropanol (CAS 67-63-0)

US. Rhode Island RTK

Isopropanol (CAS 67-63-0)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

2021-04-27

Version #

04

Effective date

2021-04-27

Other information

For an updated SDS, contact the supplier/mfr listed on the first page of the doc

